



# ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

www.ultra-infiltrant.com • 13111 Penneagle Drive, Carmel, IN, 46033 • 888-ULTRA-55

## CERTIFICATE OF COMPLIANCE / STATEMENT OF COMFORMITY

**Alloy: Ultra Infiltrant Proprietary Alloy**

**Patent No: 7341093**

Mfg Date: 12/10/09 Ship Date: 12/11/09 Order No.: 75653 Item ID: 8894

Heat #: 1) 108996 B189 B190 B191 B192  
2) B193  
3)

Elongation: 0 to 0

Cross-Sec: Round Dimension: .185 (+) .0010 (-) .0010

Temper: H66 Tensile PSI: 1 to 999999

### Chemistry Specification

Copper:	Remainder	
Zinc:	5.20 - 7.30%	5.90% Target
Manganese:	0.20 - 0.80%	.50% Target
Iron:	1.75 - 2.75%	2.00% Target
Nickel:	.10 - .30%	.20% Target
Tin:	Trace	.01% Maximum
Phosphorous:	Trace	.01% Maximum
Lead:	Trace	.01% Maximum
Aluminum:	Trace	.01% Maximum

### Mechanical Data

Diameter: .1847 to .1848

Meets Chemistry & Mechanical  
Specification

Ultra Infiltrant Produced  
in the USA

Paul A. Rivest, CEO

