



ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

ultra-infiltrant.com - 1868 Corniche Drive, Zionsville, IN 46077 - 888-ULTRA-55

CERTIFICATE OF COMPLIANCE / STATEMENT OF CONFORMITY

Alloy: Ultra Infiltrant Proprietary Alloy

Patent No: 7341093

Mfg. Date: 12/21/2010 Ship Date: 1/5/2011 Order No: 79765 Item ID: 80801

Heat #: 1) 204506 B333 B334 B354
2)
3)

Elongation: 0 to 0

Cross-Sec: Square Dimension: 0.228 (+) 0.0030 (-) 0.0030

Temper: O61 Tensile PSI: 40000 to 90000

Chemistry Specification


Copper:	Remainder		
Zinc:	3.21% - 3.54%	3.38%	Target
Manganese:	0.60% - 0.80%	0.70%	Target
Iron:	1.81% - 1.94%	1.88%	Target
Nickel:	0.20% - 0.60%	0.40%	Target
Tin:	Trace		Maximum
Phosphorous:	Trace		Maximum
Lead:	Trace		Maximum
Aluminum:	Trace		Maximum
Silicon:	Trace		Maximum

Mechanical Data

Diameter: 0.2259 to 0.2275

Meets Chemistry & Mechanical Specification

Ultra Infiltrant Produced in the USA



Paul A. Rivest, CEO