



# ULtra INFILtrant

YOUR WROUGHT/WIRE INFILTRATION SOLUTION.

www.ultra-infiltrant.com • 13111 Penneagle Drive, Carmel, IN, 46033 • 888-ULTRA-55

## CERTIFICATE OF COMPLIANCE / STATEMENT OF COMFORMITY

**Alloy: Ultra Infiltrant Proprietary Alloy**

**Patent No: 7341093**

Mfg Date: 06/06/09 Ship Date: 08/31/09 Order No.: 73967 Item ID: 8895

Heat #: 1) 105652 B109 B110  
2)  
3)

Elongation: 0 to 0

Cross-Sec: Square Dimension: .228 (+) .0030 (-) .0030

Temper: O61 Tensile PSI: 40000 to 90000

### Chemistry Specification

Copper:	Remainder	
Zinc:	5.20 - 7.30%	5.90% Target
Manganese:	0.20 - 0.80%	.50% Target
Iron:	1.75 - 2.75%	2.00% Target
Nickel:	.10 - .30%	.20% Target
Tin:	Trace	.01% Maximum
Phosphorous:	Trace	.01% Maximum
Lead:	Trace	.01% Maximum
Aluminum:	Trace	.01% Maximum

### Mechanical Data

Diameter: .2284 to .2290

Meets Chemistry & Mechanical  
Specification

Paul A. Rivest, CEO

Ultra Infiltrant Produced  
in the USA

